

# Certificate of conformity of the factory production control

## 1245-CPR-0104

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

## **Machine Graded Softwood Structural Timber**

With rectangular cross section for joists, posts, studs, beams, roof timbers for buildings and bridges produced under factory production control and the continuous surveillance, assessment and evaluation of the factory production control under system 2+

produced by

## Sia Vika Wood

and produced in the manufacturing plant

# Punti, Laucienas pagasts, Talsu Rajons, Latvia

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)

# EN 14081-1:2005 + A1:2011

under system 2+ are applied and that the factory production control fulfils all the prescribed requirements set out above.

This certificate was first issued on 18 December 2019 and will remain valid as long as the test methods and/or factory production control requirements included in the harmonised standard, used to assess the performance of the declared characteristics, do not change, and the product, and the manufacturing conditions in the plant are not modified significantly.

Gail Sumner Director Morecambe

18 December 2019



0140

This certificate remains valid subject to twelve monthly surveillance audits as applicable to the standard/s and that the above certificate holder provides products and services in strict adherence to the above standard/s and does not change or amend their products and services. Product liability is the responsibility of the above certificate holder and CATG cannot accept any responsibility.



1245

**SIA Vika Wood** 

13

1245-CPR-0104

Graded structural timber with rectangular cross section M/LV/Dry Graded/WPPA

Dimensions of cross section: As delivery notes

BS EN 14081-1:2005 + A1:2011

Strength grade of timber: C16 - C30; TR26

Reaction to fire: D-s2, d0

Release of dangerous substances: NPD

Natural durability (not treated): Class 4

**Durability for treated timber: NPD** 

Wood destroying fungi: Class 4

Insects: NPD
Termites: NPD

Marine borers: NPD





# **Construction Products Regulation**

## **DECLARATION OF PERFORMANCE**

No: 1245-CPR-0104

1. Unique identification code of the product-type:

C16; C18; C24; C30 and TR26 strength graded softwood

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Invoice numb	er:	
--------------	-----	--

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

#### Structural timber to be used for studs, joists, purlins, rafters and beams

4. Name, registered trade name or registered trademark and contact address of the manufacturer as required pursuant to Article 11(5):

SIA "Vika Wood"
"Punti" Laucienes pagasts
Talsu novads
LV-3285
Latvija
Tel +371 63291800

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

#### Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

#### BS EN 14081-1:2005 + A1:2011

CATG 1245 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control under system 2+ and issued the certificate of constancy of conformity of the factory production control

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

#### Not applicable

9. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
Strength grade of timber	C16 - C30; TR26	
Reaction to fire	D-s2, d0	
Release of dangerous	NPD	
substances		_
Natural durability (not treated)	Class 4	
Durability for treated timber	NPD	EN 14081:2005 +A1:2011
Wood destroying fungi	Class 4	
Insects	NPD	
Termites	NPD	
Marine borers	NPD	

Specific technical documentation:

#### Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Haralds Kronbergs Managing director

Name; surname

Position

Signature