CATG CERTIFICATION & EXAMINATION

Certificate of conformity of the factory production control

1245-CPR-0104

This certificate applies to the construction product

Strength graded structural timber with rectangular cross Section

With rectangular cross section for joists, posts, studs, beams, roof timbers for buildings and bridges produced under factory production control and the continuous surveillance, assessment and evaluation of the factory production control under system 2+ produced by

Sia Vika Wood

and produced in the manufacturing plant

Punti, Laucienas Pag, Talsu Rajons, Latvia

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)

EN 14081-1:2005+A1:2011

under system 2+ are applied and that the factory production control fulfils all the prescribed requirements set out above. This certificate was first issued on 01 January 2021 and will remain valid if the test methods and/or factory production control requirements included in the harmonised standard, used to assess the performance of the declared characteristics, do not change, and the product, and the manufacturing conditions in the plant are not modified.

Gail Sumner

Gail Sumner
Director
Morecambe
01 January 2021

UK CA
1245

UKAS PRODUCT CERTIFICATION
0140

This certificate remains valid subject to twelve surveillance audits as applicable to the standard/s and that the above manufacturer produces products in strict adherence to the above standard and CPR and does not change or amend their products and their FPC. Product liability is the responsibility of the above company and CATG cannot accept any responsibility. Full details are available from: **CATG Ltd., 29a Princes Crescent, Morecambe, Lancashire, LA4 6BY. T: 01524 400632, E: sales@catg.co.uk**

Declaration accompanying commercial documents

UK CA **1245**
SIA Vika Wood **13** **1245-CPR-0104**
Graded structural timber with rectangular cross section M/LV/Dry Graded/WPPA **Dimensions of cross section: As delivery notes** **BS EN 14081-1:2005 + A1:2011**
Strength grade of timber: C16 – C30; TR26
Reaction to fire: D-s2, d0
Release of dangerous substances: NPD
Natural durability (not treated): Class 4
Durability for treated timber: NPD
Wood destroying fungi: Class 4
Insects: NPD
Termites: NPD
Marine borers: NPD

Construction Products Regulation

DECLARATION OF PERFORMANCE

No: 1245-CPR-0104

1. Unique identification code of the product-type:

C16; C18; C24; C27; C30 and TR26 strength graded softwood

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Invoice number: _____

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Structural timber to be used for studs, joists, purlins, rafters and beams

4. Name, registered trade name or registered trademark and contact address of the manufacturer as required pursuant to Article 11(5):

SIA "Vika Wood"
"Punti" Laucienes pagasts
Talsu novads
LV-3285
Latvija
Tel +371 63291800

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 2+

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

BS EN 14081-1:2005 + A1:2011

CATG 1245 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control under system 2+ and issued the certificate of constancy of conformity of the factory production control

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not applicable

9. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
Strength grade of timber	C16 – C30; TR26	
Reaction to fire	D-s2, d0	
Release of dangerous substances	NPD	
Natural durability (not treated)	Class 4	
Durability for treated timber	NPD	EN 14081:2005 +A1:2011
Wood destroying fungi	Class 4	
Insects	NPD	
Termites	NPD	
Marine borers	NPD	

Specific technical documentation:

Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Haralds Kronbergs	Managing director	
Name; surname	Position	Signature

SIA "VIKA WOOD"
SABIEDRĪBA AR IERobEŽOTU ATBILDĪBU
COMPANY WITH A LIMITED LIABILITY